



Model 1000HP-SF

## MODEL 1000HP-SF

### High Pressure Steam Reducing Regulator

A special variation of the basic Model 1000HP pressure reducing regulator enables the Model 1000HP-SF to contain high inlet pressures up to 2600 psig (179.3 Barg) SWP, while controlling downstream pressures between 100 and 300 psig (6.9 and 20.7 Barg). Available in sizes 1/2", 3/4" and 1" (DN15, 20 and 25) with NPT connections.

### FEATURES

- Wrought barstock cylinder.
- Integral seat.
- Stellite seat surfaces.
- Reduced port.
- Very high pressure drop capability.

### APPLICATIONS

Primarily used in high pressure saturated steam systems.

### STANDARD/GENERAL SPECIFICATIONS

<b>Body Sizes:</b>	1/2", 3/4" and 1". (DN15, DN20 and DN25).
<b>End Conn:</b>	NPT female.
<b>Body/Spring Chamber Material:</b>	Carbon Steel – Body: ASTM A216, Gr. WCC Spg Chamber: ASTM A216, Gr. WCB

<b>Trim Design:</b>	S1 trim, 316 SST, Integral, Stellite Metal Seat, 316 SST Bar Stock Cylinder, 302 SST Diaphragm.
	<u>1/2" (DN15) size:</u> One-Step reduced port.
<b>Design Inlet</b>	<u>3/4" &amp; 1" (DN20 &amp; DN25) sizes:</u> Two-Step double reduced port.



**Pressure:** 2600 psig (179.3 Barg), Saturated Steam.

**Temperature Range:** -20° to 700°F (-28.6° to 371.4°C) at inlet.

**Design Outlet Pressure:** 350 psig (24.1 Barg).

**Range Springs:** Epoxy Coated Steel.

**Gaskets:** Std. – Carbon graphite.

**Diaphragm Flange Bolting:** High strength, zinc plated heat treated steel.  
Nuts - Gr. 2H.  
Studs - Gr. B7.

**Painting:** All non-corrosion resistant portions to be painted with corrosion resistant epoxy paint per Cashco Spec #S-1606.

**Seat Leakage:** Meets ANSI/FCI 70-2, Class IV.

Body Size		Range Spring	
in	(DN)	psig	(Barg)
1/2"	(15)	150-300	(10.3-20.7)
3/4"	(20)	140-300	(9.6-20.7)
1"	(25)	100-300	(6.9-20.7)

**NOTE:** Not for use in dead-ended applications. Installations should include a suitable overprotection device immediately downstream of this regulator.

**MAXIMUM CAPACITY - Cv  
FOR SIZING RELIEF DEVICE (with plug wide open)**

Body Size		Orifice Size		Cv
1/2"	(DN15)	3/8"	(9.5 mm)	3
3/4"	(DN20)	3/8"	(9.5 mm)	4
1"	(DN25)	1/2"	(12.7 mm)	6

Metric Conversion Factor: Cv x 1.16 = kv

**FLOW CAPACITY  
Cv vs. DROOP**

Outlet Pressure		Size 1/2" (DN15) One-Step		Size 3/4" (DN20) Two-Step		Size 1" (DN25) Two-Step	
		CV @ % Droop		CV @ % Droop		CV @ % Droop	
psig	(Barg)	10%	20%	10%	20%	10%	20%
100	(6.9)	--	--	--	--	1.27	2.36
150	(10.3)	1.18	2.04	1.18	2.04	1.40	2.48
200	(13.8)	1.28	2.13	1.28	2.13	1.58	2.64
250	(17.2)	1.37	2.21	1.37	2.21	1.67	2.72
300	(20.7)	1.45	2.29	1.45	2.29	1.77	2.88

Metric Conversion Factor: Cv x 1.16 = kv

The contents of this publication are presented for informational purposes only, and while every effort has been made to ensure their accuracy, they are not to be construed as warranties or guarantees, express or implied, regarding the products or services described herein or their use or applicability. We reserve the right to modify or improve the designs or specifications of such product at any time without notice. Cashco, Inc. does not assume responsibility for the selection, use or maintenance of any product. Responsibility for proper selection, use and maintenance of any Cashco, Inc. product remains solely with the purchaser.

Product Code				12-06-13
Body Size		Complete Unit	Parts Rebuild Kit	
in	(DN)	Product Code	Kit Code	
1/2"	(15)	BG4-5S17-1FX33008A	A99-80-K-33008-00A	
3/4"	(20)	BG5-5S17-1JX33138A	A99-80-K-33138-00A	
1"	(25)	BG6-5S17-1KX33009A	A99-80-K-33009-00A	

Cashco, Inc.  
P.O. Box 6  
Ellsworth, KS 67439-0006  
PH (785) 472-4461  
Fax. # (785) 472-3539  
www.cashco.com  
email: sales@cashco.com  
Printed in U.S.A. 1000HP-SF-TB

Cashco GmbH  
Handwerkerstrasse 15  
15366 Hoppegarten, Germany  
PH +49 3342 4243135  
PH +49 3342 4243136  
www.cashco.com  
Email: germany@cashco.com

Cashco do Brasil, Ltda.  
Al.Venus, 340  
Indaiatuba - Sao Paulo, Brazil  
PH +55 11 99677 7177  
Fax. No.  
www.cashco.com  
Email: brazil@cashco.com